

NOVITA Super

33294 – Novita Super with flat base



Flat base
For cutting all kinds of material
in the outer wear industry

78825 – Extension (80cm long)
This machine is also available
with an extension.

NOVITA Super

APPLICATION AREA

The „Novita Super“ provides concentrated force to withstand heavy and even the most difficult of loads. The cutting performance is 10x greater than that of the Novita Standard version. Particularly handy and lightweight machine for cutting all types of material in layers up to approx. 8 mm high, depending on the material.

Particularly suitable for needled felt, Skai, branded films, soft leather and upholstery cover materials. The lubricator reduces friction between the blade and the counter blade, enabling laminated goods to be cut.

Cutting machine for template and pattern making, cutting single layers, re-cutting defectives parts, straight cutting true to form, light load (outer wear materials, knitted goods and knitwear, curtain, upholstery and decoration fabrics etc.).

The blade protection in signal colour can be adjusted easily and infinitely and does not constrict the visibility. The actuating lever for the grinding device is well shaped, so that the blade can be re-sharpened with one hand even during cutting. Handling and guidance of the machine is easy and balanced.



25508 - Skid base
For cutting thicker materials (upholstery etc.) and for an exact template cut.



28456 - Skid base with protective ball
For cutting delicate materials (no fibre damage)

TECHNICAL DATA:

Motor power:	approx. 56 Watt
Motor data:	220 V / 50 Hz
Operating time:	60 % (no non-stop operating)
Motor speed (idle):	approx. 12.500 U/min
Blade speed (idle):	approx. 1.500 U/min
Blade diameter:	50 mm
Blade wear limit:	approx. 42 mm
Cutting height, max.:	8 mm
Motor diameter:	approx. 50 mm
Machine length:	approx. 260 mm
Machine weight, excl. cable:	approx. 1.000 g
Vibration:	< 2,5 m/s
Running noise:	73 dB(A)

WWW.KURIS.DE